

Pinout V320BJ8-Q01 32'in. LCD Display

Number	Name	Description	
1.	VCC	+12V	
2.	VCC	+12V	
3.	VCC	+12V	
4.	VCC	+12V	
5.	NC	NOT USED	
6.	GND	GROUND	
7.	GND	GROUND	
8.	NC	NOT USED	
9.	SEL.LVDS	LVDS DATA FORMAT SELECTION	
10.	NC	NOT USED	
11.	GND	GROUND	
12.	RX0-	Negative transmission of data pixel 0	
13.	RX0+	Positive transmission of data pixel 0	
14.	GND	GROUND	
15.	RX1-	Negative transmission of data pixel 1	
16.	RX1+	Positive transmission of data pixel 1	
17.	GND	GROUND	
18.	RX2-	Negative transmission of data pixel 2	
19.	RX2+	Positive transmission of data pixel 2	
20.	GND	GROUND	
21.	RXCLX-	CLOCK -	
22.	RXCLK+	CLOCK +	
23.	GND	GROUND	
24.	RX3-	Negative transmission of data pixel 3	
25.	RX3+	Positive transmission of data pixel 3	
26.	GND	GROUND	
27.	NC	NOT USED	
28.	C_SCL	I2C CLOCK (for auto v-com)	
29.	C_SDA	I2C DATA (for auto v-com)	
30.	GND	GROUND	